

## NOTES:

- MINIMUM DIMENSIONS PROVIDED. CONTRACTOR SHALL INCREASE AS NEEDED TO ADJUST OR REPLACE MANHOLE COVER, FRAME, OR CONCRETE RINGS.
- SAWCUT EDGE OF EXISTING PAVEMENT THE SAME DISTANCE AROUND EXISTING MANHOLE RING AND COVER TO PRODUCE A SMOOTH AND EVEN EDGE FOR SURFACE REPLACEMENT.
- CONTRACTOR SHALL PROTECT SEWER FROM CONSTRUCTION DEBRIS.
- ANY DEBRIS WHICH ENTERS THE MANHOLE OR THE SEWER MAIN SHALL BE IMMEDIATELY REMOVED BY CONTRACTOR.
- REUSE MANHOLE RING AND COVER EXCEPT PER NOTE 6.
- EXISTING MANHOLE RING AND COVER OR CONCRETE RINGS DAMAGED BY CONSTRUCTION SHALL BE REPLACED AT CONTRACTOR'S EXPENSE AS PER CITY OF WACO DETAILS. REFER TO \$-6, \$-7, \$-8, \$-9, S-10, SD-9 FOR APPLICABLE REQUIREMENTS.
- EXISTING MANHOLE RING AND COVER OR CONCRETE RINGS DESIGNATED FOR REPLACEMENT SHALL BE DONE SO BY THE CONTRACTOR PER NOTE 6.
- SEE CITY OF WACO DETAIL S-5 FOR ADDITIONAL REQUIREMENTS.
- MANHOLE LID SHALL BE FLUSH WITH FINISHED PAVEMENT SURFACE. MAX TOLERANCE +/- 1/8 INCH.

## MANHOLE LID HEIGHT ADJUSTMENT OR REPLACEMENT (PRESERVATION WORK ONLY)

(NO SCALE)



ENG	INE	ER	ING	DIV	/ISI	ON
ISCLAIMER:	THE USE	OF THIS	STANDARD	IS GOVER	NED BY T	HE "TEXAS
NGINEERING	PRACTIC	E ACT". N	IO WARRAI	NTY OF AN	IY KIND IS	MADE BY
HE CITY OF V	VACO FOR	ANY PUR	POSE WHA	TSOEVER.	THE CITY	OF WACO
SSUMES NO	RESPONS	IBILITY FO	OR THE CO	NVFRSION	OF THIS:	STANDARD

THE "TEXAS	
INE LEVAS	
S MADE BY	
Y OF WACO	
STANDARD	
-	
DAMAGES	
	##

REVISIONS					
NO.	COMMENTS	BY	DATE	ı	
				ı	
				L	
				Г	
				ı	
				ı	
##	DESCRIPTION	FL	MM/DD/YYYY	ı	

DATE 11/15/2024