



## PAVEMENT / SURFACE REPLACEMENT DETAILS

- ① SEE [ST-30](#) FOR CONCRETE OR [ST-31](#) FOR CONTROLLED LOW STRENGTH MATERIAL AND APPLICABLE [ST-33](#) AND/OR [ST-34](#) FOR SAW CUT AND PAVEMENT REPLACEMENT DETAILS.
- ② SEE [ST-37](#) AND APPLICABLE [ST-35](#) AND/OR [ST-36](#) FOR SAW CUT AND PAVEMENT REPLACEMENT DETAILS.
- ③ TYPE "A" MATERIAL PER STANDARD SPECIFICATIONS FOR CONSTRUCTION, SECTION 4.2 EXCAVATION AND BACKFILL, PART 2: PRODUCT, A. MATERIALS, 3. TRENCH BACKFILL, A. TYPE "A." MATERIAL MECHANICALLY COMPACTED TO 95% OF THE MAXIMUM DRY DENSITY (TEX-113-E) OR CONTROLLED LOW STRENGTH MATERIAL.
- ④ USE CONTROLLED LOW STRENGTH MATERIAL TO BACKFILL ALL TRENCHES 18 IN. OR NARROWER, IN THE RIGHT-OF-WAY AND PUBLIC EASEMENTS.
- ⑤ EDGE TO BE STRAIGHT, SQUARE AND PARALLEL TO SIDES OF TRENCH.
- ⑥ 6 IN. MIN. TOPSOIL AND SEED OR SOD - SUBSIDIARY.
- ⑦ TXDOT ITEM 247 FLEXIBLE BASE TYPE A GRADE 1-2 MINIMUM PLASTICITY INDEX 5.
- ⑧ SEE [G-10](#) FOR BACKFILL MATERIAL REQUIREMENTS AND FOR INSTALLATION.



### ENGINEERING DIVISION

**DISCLAIMER:** THE USE OF THIS STANDARD IS GOVERNED BY THE "TEXAS ENGINEERING PRACTICE ACT". NO WARRANTY OF ANY KIND IS MADE BY THE CITY OF WACO FOR ANY PURPOSE WHATSOEVER. THE CITY OF WACO ASSUMES NO RESPONSIBILITY FOR THE CONVERSION OF THIS STANDARD TO OTHER FORMATS OR FOR INCORRECT RESULTS OR DAMAGES RESULTING FROM ITS USE.

REVISIONS			
NO.	COMMENTS	BY	DATE
1	MODIFY NOTE 1	MZ	04/19/2024
##	DESCRIPTION	FL	MM/DD/YYYY

DATE  
01/01/2024

G-9