

SEDIMENTATION OUTLET PIPE

| RISER PIPE NOMINAL DIA. (IN.) | VERTICAL SPACING BETWEEN ROWS (CENTER TO CENTER) (IN.) | NUMBER OF PERFORATIONS PER ROW | DIAMETER OF PERFORATIONS (IN.) |
|-------------------------------------|---|--------------------------------------|--------------------------------------|
| 8 | 4 | 6 | 1 |
| 10 | 4 | 8 | 1 |
| 12 | 4 | 10 | 1 |

PERFORATED RISER PIPES TABLE

SEDIMENTATION OUTLET STRUCTURE: OUTLET PIPE AND PERFORATED RISER PIPE TABLE

SEE WP-9A FOR ADDITIONAL **DETAILS**

(NO SCALE)



| (| | | | | |
|--|-----|-------------|------|------------|------------|
| ENGINEEDING BIVIOLON | | REVISIONS | DATE | | |
| ENGINEERING DIVISION | NO. | COMMENTS | BY | DATE | |
| DISCLAIMER: THE USE OF THIS STANDARD IS GOVERNED BY THE "TEXAS ENGINEERING PRACTICE ACT". NO WARRANTY OF ANY KIND IS MADE BY | | | | | 04/28/2025 |
| THE CITY OF WACO FOR ANY PURPOSE WHATSOEVER. THE CITY OF WACO ASSUMES NO RESPONSIBILITY FOR THE CONVERSION OF THIS STANDARD | | | | | W/D OB |
| TO OTHER FORMATS OR FOR INCORRECT RESULTS OR DAMAGES RESULTING FROM ITS USE. | ## | DESCRIPTION | FL | MM/DD/YYYY | VVP-9D |