



NOTES:

- 1. THE CITY OF WACO BENCHMARKS SHALL BE PLACED AT A MAXIMUM SPACING OF 750 FT.
- 2. THE CITY OF WACO ENGINEERING DEPT. WILL PROVIDE THE BENCHMARKS. THE CONTRACTOR WILL COORDINATE WITH THE ENGINEERING CONSTRUCTION INSPECTOR.
- 3. THE CITY OF WACO SURVEY DEPT. MAY SUPPLY ONE "CITY OF WACO BENCHMARK" FOR PLACEMENT IN INLET TOP IN EITHER BACK CORNER.

THE CITY OF WACO SURVEY DEPT. WILL PLACE "CITY OF WACO BENCH MARK" INTO THE CONCRETE CYLINDER.

CONCRETE CYLINDER FOR BENCHMARKS

(NO SCALE)



ENGINEERING DIVISION

DISCLAIMER: THE USE OF THIS STANDARD IS GOVERNED BY THE "TEXAS ENGINEERING PRACTICE ACT". NO WARRANTY OF ANY KIND IS MADE BY THE CITY OF WACO FOR ANY PURPOSE WHATSOEVER. THE CITY OF WACO ASSUMES NO RESPONSIBILITY FOR THE CONVERSION OF THIS STANDARD TO OTHER FORMATS OR FOR INCORRECT RESULTS OR DAMAGES RESULTING FROM ITS USE.

REVISIONS					
	NO.	COMMENTS	BY	DATE	
,					
,					
)					
)					
3					
	##	DESCRIPTION	FL	MM/DD/YYYY	

DATE 01/01/2024

G-11