

NOTES:

1. CONCRETE REINFORCEMENT (NOT SHOWN FOR CLARITY) SHALL STOP 3 IN. CLEAR OF JOINT FACES.
2. SMOOTH DOWELS SHALL BE LEVEL AND PERPENDICULAR TO THE FACE.

CONCRETE EXPANSION JOINT DETAIL

(SPACED AS PER PLANS)

(NO SCALE)



NOTES:

1. SAW JOINTS AS SOON AS IT IS POSSIBLE TO DO SO WITHOUT DAMAGING THE PAVEMENT AND LESS THAN 24 HOURS AFTER CONCRETE PLACEMENT. THE EXACT TIME IS SUBJECT TO APPROVAL BY THE CITY ENGINEER.

CONCRETE STREET SAWED CONTRACTION JOINT DETAIL

(SPACED AS PER PLANS)

(NO SCALE)

CITY OF WACO

ENGINEERING DIVISION

DISCLAIMER: THE USE OF THIS STANDARD IS GOVERNED BY THE "TEXAS ENGINEERING PRACTICE ACT". NO WARRANTY OF ANY KIND IS MADE BY THE CITY OF WACO FOR ANY PURPOSE WHATSOEVER. THE CITY OF WACO ASSUMES NO RESPONSIBILITY FOR THE CONVERSION OF THIS STANDARD TO OTHER FORMATS OR FOR INCORRECT RESULTS OR DAMAGES RESULTING FROM ITS USE.

REVISIONS

NO.	COMMENTS	BY	DATE
##	DESCRIPTION	FL	MM/DD/YYYY

DATE 01/01/2024

ST-9