

NOTES:

- (1) SEE <u>G-7</u>, <u>G-8</u>, <u>G-9</u>, AND <u>G-10</u> FOR MATERIAL REQUIREMENTS AND INSTALLATION.
- (2) CONCRETE MINIMUM 2,000 PSI.

 CLASS A INDUSTRIAL COLLECTOR & ARTERIAL = 12 IN.

 CLASS B RESIDENTIAL COLLECTOR & COMMERCIAL COLLECTOR = 10 IN.

 CLASS C LOCAL STREET = 8 IN.
- (3) SAW CUT EDGE OF EXISTING PAVEMENT ON ALL SIDES OF TRENCH TO PRODUCE A SMOOTH AND EVEN EDGE FOR SURFACE REPLACEMENT. EXISTING PAVEMENT SHOULD BE REMOVED TO CLEAN, STRAIGHT LINES PARALLEL AND PERPENDICULAR TO THE FLOW OF TRAFFIC. DO NOT CONSTRUCT PATCHES WITH ANGLED SIDES AND IRREGULAR SHAPES.
- (4) SEE <u>ST-33</u> AND/OR <u>ST-34</u> FOR LIMITS OF THIS SAW CUTTING.
- (5) BONDING COURSE OF AE-P OR PRE-APPROVED EQUAL SHALL BE APPLIED TO SWEPT SURFACE AND ALLOWED TO BREAK.
- (6) CLASS A INDUSTRIAL COLLECTOR & ARTERIAL: HMAC (TYPE D) MATCH EXISTING SURFACE THICKNESS WITH 3 IN. MINIMUM (GREATER THAN 3 IN. REQUIRES MORE THAN 1 LIFT).

 CLASS B RESIDENTIAL COLLECTOR & COMMERCIAL COLLECTOR: HMAC (TYPE D) MATCH EXISTING SURFACE THICKNESS WITH 2 IN. MINIMUM.

 CLASS C LOCAL STREET: HMAC (TYPE D) MATCH EXISTING SURFACE THICKNESS WITH 2 IN. MINIMUM.
- 7 IF BASE REPLACEMENT IS WITHIN 3 FT. OF PAVEMENT EDGE OR APPURTENANCE (CURB AND GUTTER, VALLEY GUTTER, ETC.), LIMITS OF CONCRETE AND SURFACE SHALL EXTEND TO PAVEMENT EDGE OR APPURTENANCE.

CLASS A, B & C (ASPHALTIC) PAVEMENT REPLACEMENT, TRENCH BACKFILL, & EMBEDMENT

(NO SCALE)



		NEV.	
ENGINEERING DIVISION	NO.	COMMENTS	
DISCLAIMER: THE USE OF THIS STANDARD IS GOVERNED BY THE "TEXAS			
ENGINEERING PRACTICE ACT". NO WARRANTY OF ANY KIND IS MADE BY			
THE CITY OF WACO FOR ANY PURPOSE WHATSOEVER. THE CITY OF WACO			
ASSUMES NO RESPONSIBILITY FOR THE CONVERSION OF THIS STANDARD			
TO OTHER FORMATS OR FOR INCORRECT RESULTS OR DAMAGES			
RESULTING FROM ITS USE.	##	DESCRIPTION	

REVISIONS				
NO.	COMMENTS	BY	DATE	
##	DESCRIPTION	FL	MM/DD/YYYY	

DATE 01/01/2024

ST-30