COMMERCIAL DRIVE APPROACH GENERAL NOTES

NOTES:

- 1. COMMERCIAL TYPE DRIVE APPROACHES AND TURN-OUTS (I.E. FOR BUSINESS PROPERTY) REQUIRE CITY TRAFFIC APPROVAL.
- 2. WHEN CONSTRUCTING DRIVE AT EXISTING CURB, CURB MUST BE SAWED. IF THE RADIUS RETURN IS WITHIN 3 FT. OF AN EXISTING JOINT, THE EXISTING CURB AND GUTTER SHALL BE REMOVED AND REPLACED TO THE NEXT EXISTING JOINT.
- 3. ON CONCRETE STREETS: EXPANSION JOINT WITH DOWELS 3/4 IN. Ø X 24 IN. LONG SMOOTH DOWEL BARS WITH 3/4 IN. Ø PVC PIPE SLEEVE WITH CAPPED END. (REF ST-9)
- 4. EXPANSION JOINT: 2 EACH 3/4 IN. Ø X 24 IN. LONG SMOOTH DOWEL BARS WITH 3/4 IN. Ø PVC PIPE SLEEVE WITH CAPPED END. WHEN ADDING TO EXISTING DRIVE APPROACH, JOINT MUST BE SAW-CUT. REF. ST-9 FOR ADDITIONAL REQUIREMENTS.
- 5. EXPANSION JOINT WITH 3/4 IN. Ø X 24 IN. LONG SMOOTH DOWEL BARS WITH 3/4 IN. Ø PVC PIPE SLEEVE WITH CAPPED END AT 36 IN. OC. (REF_ST-9)
- 6. THE DRIVEWAY SLOPE IN THE FIRST 10 FEET FROM THE GUTTER LINE SHALL BE A MAXIMUM OF 5%. THE SLOPE MAY RISE AN ADDITIONAL 5% OR FALL A MAXIMUM OF 6% IN THE SECOND 10 FEET. THROUGH DRIVE APRON AT EXISTING OR FUTURE SIDEWALKS, MAX SLOPE SHALL BE 1.5%
- 7. A LONGITUDINAL CONTRACTION JOINT SHALL BE PLACED AT CENTERLINE OF ALL DRIVEWAYS AND ADDITIONAL LONGITUDINAL CONTRACTION JOINTS SHALL BE PLACED, SPACED EQUALLY AT 10 FT. MAXIMUM SPACING.
- 8. SEE ST-4 STANDARD ALLEY SECTION FOR ADDITIONAL INFORMATION WHEN CONNECTING TO A COMMERCIAL ALLEY.
- 9. SIDEWALK: SEE CODE OF ORDINANCES FOR REQUIREMENTS OF SIDEWALK.

 LOCATIONS WITHIN THE CODE OF ORDINANCES OF MINIMUM REQUIRED WIDTHS OF SIDEWALK AND RELATED BUFFER PRESENTLY
 INCLUDE THE FOLLOWING
 - SEC. 22-37. CHANGING OF GRADE OF STREETS, ETC.
 - SEC. 22-63. SAME-LOCATION AND WIDTH OF SIDEWALKS.
 - SEC. 28-880.11. PUBLIC SPACES.
 - SEC. 28-839. SIDEWALKS.
 - SUBDIVISION ORDINANCE SEC. 5.2. PERMANENT IMPROVEMENTS.5.207. SIDEWALKS
- 10. MINIMUM 8 IN REINFORCED CONCRETE WITH #4 BARS AT 18 IN. OCEW (CONCRETE CHAIRS REQUIRED). CONTINUOUS THROUGH DRIVE APPROACH, DRIVE APRON, AND SIDEWALK.
- 11. DRIVE APRON AT EXISTING AND FUTURE SIDEWALKS. MAX SLOPE OF 1.5% FORMED. ANY SLOPE EXCEEDING 2% SHALL NOT BE ACCEPTED.
- 12. 4 IN. TYPE "A" MATERIAL PER STANDARD SPECIFICATIONS FOR CONSTRUCTION SECTION 4.2 EXCAVATION AND BACKFILL PART 2: PRODUCT A. MATERIALS 3. TRENCH BACKFILL A. TYPE "A" OR 4 IN. RECYCLED CRUSHED CONCRETE (TXDOT STANDARD SPECIFICATIONS FOR CONSTRUCTION ITEM 247 FLEXIBLE BASE TYPE D, GRADE 1-2 EXCLUDING TYPE A MATERIALS, WITH A MINIMUM P.I. OF FOUR) OR 4 IN. PORTLAND CEMENT TREATED BASE (AFTER COMPACTION COVERED BY 10 MIL POLYETHELENE BOND BREAKER) MECHANICALLY COMPACTED TO 95% OF THE MAXIMUM DRY DENSITY.
- 13. UPON REQUEST, CONTRACTOR SHALL SHOW INSPECTOR SIDEWALK COMPLIANCE.
- 14. IF DISTANCE BETWEEN INITIALLY REQUIRED TRANSVERSE JOINTS EXCEEDS 10 FT. THEN ADDITIONAL CONTRACTION JOINT(S) SHALL BE PLACED TO ENSURE DISTANCE BETWEEN TRANSVERSE JOINTS DOES NOT EXCEED 10 FEET. THESE ADDITIONALLY REQUIRED CONTRACTION JOINTS SHALL BE PLACED TO PROVIDE EQUAL SPACING BETWEEN TRANSVERSE JOINTS TO THE EXTENT PRACTICAL.
- 15. CONTRACTION JOINT MAY BE TOOLED. SEE ST-9 FOR DETAILS.

COMMERCIAL DRIVEWAY STANDARDS								
DRIVEWAY TYPE	"W"	"R"						
DRIVEWAY TYPE	DRIVEWAY WIDTH	BACK OF CURB RADIUS						
ARTERIAL	30 FT MIN ~ 42 FT MAX	10 FT MIN						
COLLECTOR/LOCAL/CBD	24 FT MIN ~ 42 FT MAX	10 FT MIN 10 FT MIN ~ 25 FT MAX						
ALLEY (NOTE 8)	MATCH ALLEY R.O.W.							
INDUSTRIAL DRIVEWAY AND INTERNAL CIRCULATION STANDARDS								
DRIVEWAY TYPE	"W"	"R"						
DRIVEWATTTPE	DRIVEWAY WIDTH	BACK OF CURB RADIUS						
ARTERIAL	30 FT MIN ~ 50 FT MAX	15 FT MIN ~ 25 FT MAX						
COLLECTOR/LOCAL/CBD	30 FT MIN ~ 50 FT MAX	10 FT MIN ~ 25 FT MAX						
ALLEY (NOTE 8)	MATCH ALLEY R.O.W.	10 FT MIN ~ 25 FT MAX						
SEE CITY OF WACO DEVELOPMENT GUIDE FOR MORE DETAIL								

SEE <u>ST-24A</u> FOR ADDITIONAL DETAILS



ENGINEEDING BIVIOLON	REVISIONS				DATE
ENGINEERING DIVISION	NO.	COMMENTS	BY	DATE	
DISCLAIMER: THE USE OF THIS STANDARD IS GOVERNED BY THE "TEXAS					01/01/2024
ENGINEERING PRACTICE ACT". NO WARRANTY OF ANY KIND IS MADE BY					
THE CITY OF WACO FOR ANY PURPOSE WHATSOEVER. THE CITY OF WACO					_
ASSUMES NO RESPONSIBILITY FOR THE CONVERSION OF THIS STANDARD					CT 21D
TO OTHER FORMATS OR FOR INCORRECT RESULTS OR DAMAGES					O1-24D
RESULTING FROM ITS USE.	##	DESCRIPTION	FI	MM/DD/YYYY	1